

MiniC
Mini Bright Flashlight

Features

- Mini-might brightness, thumb-sized.
- CREE XP-L HI V3 LED, maximum output up to 600 lumens.
- Extreme runtime, up to 9 days in moon mode.
- Professional optical lens design, even-lit flood and soft beam.
- Tail magnetic base function, attach to a metal surface to provide "hands-free" illumination.
- Fade-in and Fade-out function when the turbo mode is the initial mode for on and off to promote eye safety and improve user experience.
- Newest Intelligent Temperature protection System(ITS) monitors internal temperature and adjusts output to regulate heat dissipation; protects LED and internal components for perfect balance of output and safety.
- Intelligent Battery Capacity Indicator to view remaining battery capacity at any time.
- Unique lock-out mode prevents accidental activation; avoiding battery drains during storage or travelling and prevents unintended directly shining into eyes.
- Reverse-polarity protection prevents damage due to incorrect battery orientation.
- One-touch low and with mode memory function.
- Aerospace Aluminum Alloy construction; CNC precision machining; Mil-Spec HAIII anodizing, anti-abrasive, lighter and robust.
- Compatible with CR123A and 16340 Li-ion battery.
- KLARUS high performance 16340 battery with Micro-USB port included, no need to bring a charger, easy to use, safe and reliable.

Specs

- CREE XP-L HI V3 LED, 50000 hours life.
- 4 lighting levels, 2 flashing modes.

Mode		High	Medium	Low	Moonlight	Strobe	SOS
ANSI lumens (LM) 16340	600	45	10	1	600	45	
Runtime(h) 16340	72min	37min	32h	6d	144min	15h	40min
ANSI lumens (LM) CR123A	305	45	10	1	305	45	
Runtime(h) CR123A	141min	48min	55h	9d	282min	33h	
Beam intensity(cd)	400	31	6.3	0.6			
Beam distance(m)	40	11	5	1.5			
Impact resistance(m)	1						
Waterproof	IPX8(underwater 2 meters)						

- Working Voltage: 2V-4.2V.
- Compatible Batteries: CR123A x 1 or 16340 Li-ion battery x 1.
- Reflector: Convex Lens.
- Switch Type: Side Switch.
- Dimension: 20.5mm (0.81") x 19.8mm (0.78") x 54.5mm (2.15").
- Net Weight: 27g (0.95oz) (w/o battery).
- Material: 6061-T6 Aluminum Alloy Body, Mil-Spec HAIII Anodizing.
- Waterproof: IPX8 (underwater 2 meters).
- Included Accessories: Spare O Ring x 1, Stainless Steel Clip x 1, 16340 Li-ion Battery with Micro-USB Charging Port x 1.

Note: The above data has been measured in accordance with international flashlight testing standards ANSI/NEMA FL1 using CRA123A Li-ion battery and KLARUS 16340 Li-ion battery under laboratory conditions. The data may vary slightly during actual use due to battery type, individual usage habits and environmental factors. KLARUS is a member of PLATO, participating in and helping to develop the ANSI/NEMA FL1 standard of measurement. Product testing data is in accordance with these internationally recognized scientific standards.

Operation

When OFF, click the side switch to enter into the last memorized mode when last powered off, click to change mode, cycle through moonlight(1LM)→Low mode(10LM)→Medium mode(45LM)→High mode(600LM) or 305LM); Long press side switch for 1S to enter into the moonlight mode when OFF.

Long press side switch for 1S to turn OFF when ON; Quick double-click the side switch to enter into strobe when the side switch is unlocked; Double click again to enter into SOS and click to exit.


Lock-Out

Long press the side switch for 5S to lock the flashlight controls. Press the side switch three times to unlock the flashlight (The lamp will flash three times to indicate status change and will flash twice to indicate the flashlight is failed to unlock).

Battery Capacity Indicator

When OFF, press the side switch three times, the main lamp flashes to indicate the battery capacity: Three times: 70%-100% capacity; Twice: 30%-70% capacity; Once: less than 30% capacity; The lamp flashes twice every three minutes when battery at less than 10% capacity, replace battery immediately; Note: The lamp will display as above only when using 16340 Li-ion batteries.

Battery Replacing



Intelligent Temperature Protection System (ITS)

During turbo mode, the brightness will be adjusted automatically according to the temperature of the flashlight body in order to protect the LED and internal components. This makes the lights safer in operation and more comfortable to hold.

Care and Maintenance

- The flashlight's surface will increase in temperature during use, especially during periods of higher lumen output. The maximum safe operating surface temperature of the flashlight is 60°C/140°F.
- Please fully charge battery before initial use. Included battery is charged to less than 50% as a safety measure and will not power the flashlight at full output.
- To maintain waterproof condition, please lubricate the O-ring with resin or oil and replace worn O-rings as needed.
- Do not shine light directly into eyes.
- For long term storage, remove the batteries and store in a cool and dry location.

Warranty

- KLARUS guarantees the flashlight against defects in material and workmanship. Flashlight products that are found to be defective under normal use within 5 years of the proof of purchase date will be repaired or replaced without charge.
- This warranty does not cover damage caused by accident, unreasonable use or product alteration. Failure to follow the general maintenance directions could result in damage to your flashlight that may not be covered by the KLARUS warranty.



Limited Lifetime Warranty

If items develop after 5 years from the date of purchase, KLARUS will charge for parts. The total

repair fee will be assessed according to the cost of the replacement materials. If damage to the light is substantial, KLARUS will contact the customer via the dealer with a quote. The customer can then decide whether to proceed with the repairs or not. Freight will be paid by dealer or customer.




Warranty Procedure



- If this flashlight does not perform to the specification, the product will be repaired or replaced as described above.
- Please contact your original KLARUS dealer for replacement and repairs.
- If the warranty issue cannot be resolved by the dealer, please contact KLARUS at info@klaruslight.com for assistance. Please provide the following information to expedite the process:
 - 1) List the serial number on the light.
 - 2) Include a detailed description identifying the issue, accompanied by pictures or a short video demonstration if necessary.
 - 3) Provide the name and store of the dealer you made the purchase from; and a copy of the proof of purchase.

Website Facebook

KLARUS LIGHTING TECHNOLOGY CO., LIMITED
Office Address: Room 521-525, Zhihugu Innovation Park, 1010 Bulong Road, Longhua District, Shenzhen City, 518131, China.
Factory Address: 5/F, No.26 Building, Niulianqiang Industrial Park, Longhua District, Shenzhen City, 518131, China.
Email: info@klaruslight.com
Phone: +86-755-27700110
Website: www.klaruslight.com

MiniC
迷你高亮手电

特点

- 迷你高亮, 拇指大小。
- 搭载美国最新原装进口CREE XP-L HI V3 LED, 亮度高达600流明。
- 超长续航, 月光模式下续航时间长达9天。
- 专业光学设计的透镜, 泛光均匀, 光线柔和不刺眼。
- 尾部磁铁功能, 可吸附在金属表面, 解放双手。
- 渐变渐灭功能, 高亮档开启和关闭时渐变渐灭, 提高眼睛适应度及使用舒适度。
- 最新ITS智能温控系统, 可实时监测内部温度变化并平滑调整最高亮度输出, 在保护LED及内部元器件的基础上提升照明性能, 达到输出性能和安全性上的良好平衡。
- 智能电量指示功能, 可随时查看剩余电量, 使用时间自由掌控。
- 特别为侧面开关设计的锁定功能, 锁定后避免在旅行包内误点亮, 也可避免小孩把玩误伤眼睛。
- 电池防反接功能, 电池正负极接反不会损坏电路。
- 一键进入最低亮, 并且手电档位带有记忆功能。
- 航天级铝合金材质, CNC机加工外壳, 军工三级硬质阳极氧化处理, 耐磨更轻更坚固。
- 兼容CR123A和16340锂离子电, 标配带Micro-USB充电口的KLARUS 16340高性能电池, 无需充电器, 使用方便, 安全可靠。

规格

- 采用美国进口CREE XP-L HI V3 LED, 寿命长达50000小时。
- 模式: 4种亮度模式, 2种闪烁模式。

ANSI/NEMA FL1		高亮	中亮	低亮	月光	爆闪	SOS
ANSI lumens (LM) 16340	600	45	10	1	600	45	
Runtime(h) 16340	72min	37min	32h	6d	144min	15h	40min
ANSI lumens (LM) CR123A	305	45	10	1	305	45	
Runtime(h) CR123A	141min	48min	55h	9d	282min	33h	
Beam intensity(cd)	400	31	6.3	0.6			
Beam distance(m)	40	11	5	1.5			
Impact resistance(m)	1						
Waterproof	IPX8(防水2m)						

- 工作电压 2.0V-4.2V。
- 电池: 1节CR123A或者1节16340锂离子电。
- 反光杯: 单凸透镜。
- 开关类型: 侧按开关。
- 尺寸: 20.5mm x 19.8mm x 54.5mm。
- 重量: 27g(不含电池)。
- 材料: 6061-T6 铝合金, 军规三级硬质阳极氧化表面处理。
- 防水: IPX8(水下2米)。
- 配件: 备用O圈 x 1, 抱夹 x 1, 带Micro-USB直充16340锂离子电 x 1。

备注: 以上参数是按照国际手电筒测量标准ANSI/NEMA FL1所述之方法测量所得, 所使用电极为高性能CR123A锂离子电和KLARUS 16340锂离子电, 实际数据可能会随着不同电或使用环境而产生影响。KLARUS是美国手电行业协会(PLATO)的成员, 参与制定和优化ANSI/NEMA FL1手电标准, 产品测试数据标准科学。

使用操作

关机时单击侧按开关进入记忆档位, 单击换挡, 依次为月光(1LM)→低亮(10LM)→中亮(45LM)→

高亮(600LM或305LM)循环。关机时长按侧按开关1S进入月光档位; 开机时长按1S关机。

侧按键不锁定时快速双击侧按进入爆闪, 再次双击进入SOS, 单击返回原来模式。

锁定功能

关机状态下长按5S侧按键, 锁定后主灯闪烁3次提示已锁定。

快速三击侧按键, 解锁后主灯闪烁3次提示按键已解锁; 如解锁不成功, 主灯闪烁2次提示解锁失败。


电量指示功能

关机状态下, 侧按开关快速单击3次主灯闪烁次数指示电池电量, 3次70%-100%, 2次30%-70%, 1次30%以下。

电量低于10%的时候主灯每隔3分钟闪2次提示用户电量不足, 需及时更换电。

注: 此电量指示功能只针对16340锂离子电。

电池更换



智能温控系统



在最高亮时, 智能温控系统会根据灯具的温度来调节输出亮度, 以保护LED及内部元器件, 更安全可靠, 同时增加手指舒适度。

使用及维护



- 灯具在使用过程中, 灯具表面温度在60°C以下属于正常情况, 请放心使用。
- 充电电出厂时只有50%以下电量, 直接使用不能达到最高亮度和正常续航时间, 首次使用请将电充满。
- 为达到最佳防水性能, 请定期检查防水O圈的完整性, 并适量涂抹润滑硅脂于防水O圈上以延长其使用寿命。
- 如O圈损坏, 请及时更换原厂O圈以确保您所使用的产品的优异防水性能。
- 请勿将灯具的光线直接照射人类或动物的眼睛。
- 长时间不使用灯具时, 请将电取出, 并妥善存放于阴凉干燥处。

保修

- 15天保换期: 自售出之日起15天内, 在正常使用情况下, 出现产品质量问题, 客户可选择更换新品或维修服务, 要求更换时, 所换产品应为返修产品同型号同规格的新品; 如同型号同规格的产品停止生产时, 则调换不低于原产品性能的同品牌产品。
- 5年免费保修期: 自售出之日起5年内, 用户在正常使用情况下, 出现产品质量问题, 可享受免费维修服务。
- 终身有限保修: 超过5年免费保修期外, 提供有偿保修, 费用以实际更换材料费用为准, 不另收取人工费。

关注微信 进入官网

京东购买 淘宝购买

深圳市凯瑞兹电子科技有限公司
销售中心: 深圳市龙华新区布龙路1010号智慧谷创新园大楼521-525
制造中心: 深圳市龙华新区民治栏前工业区26栋5楼
邮编: 518131
电话: +86-755-27700110
网站: www.klaruslight.cn
邮箱: info@klaruslight.com

